

PHONE: +86 523 8209 0500
FAX: +86 523 8209 0502



E-MAIL: Sales@maxdao.com
INTERNET: www.maxdao.com

7/16 DIN Coaxial Connectors



Electrical Characteristics		Environmental Characteristics	
Impedance	50Ω	Working temperature : -65~+165℃	
Insulation resistance (MΩ)	≥10 ⁴	Relative moisture	90%~95% (40±2℃)
VSWR (0~2GHz)	≤1.10	Atmospheric pressure 70~106Kpa	
IM3 (dBc)	≤-155	Waterproof	IP68
Contact resistance (mΩ)	Outer conductor	≤1.5	Corrosion (Salt Spray Test)
	Inner conductor	≤0.4	

Product	Cable type	Connector type	Unit	P/N
7/16 DIN connectors	3/8" S	male straight	Set	MX0101001
		female straight		MX0101002
		male right angle		MX0101003
	1/2" S	male straight		MX0101004
		female straight		MX0101005
		male right angle		MX0101006
	1/2" R	male straight		MX0101007
		female straight		MX0101008
		male right angle		MX0101009
	7/8" S	male straight		MX0101010
		female straight		MX0101011
		male right angle		MX0101012
	7/8" R	male straight		MX0101013
		female straight		MX0101014
	1 1/4" R	male straight		MX0101015
		female straight		MX0101016
	1 5/8" R	male straight		MX0101017
		female straight		MX0101018