

PHONE: +86 523 8209 0500

FAX: +86 523 8209 0502



E-MAIL: Sales@maxdao.com

INTERNET: www.maxdao.com

Coaxial Connectors Adapters



Electrical Characteristics		Environmental Characteristics	
Impedence	50Ω	Working temperature :	-65~+165℃
Insulation resistance (MΩ)	≥10 ⁴	Relative moisture	90%~95% (40±2℃)
VSWR (0~2GHz)	≤1.10	Atmospheric pressure	70~106Kpa
IM3 (dBc)	≤-155	Waterproof	IP68
Contact resistance (mΩ)	Outer conductor ≤1.5 Inner conductor ≤0.4	Corrosion (Salt Spray Test)	Continuous Mist for 48 Hours (5% NaCl)
Product	Connector interfaces	Unit	P/N
Adapters	N male-N male, straight	Set	MX0103001
	N female-N female, straight		MX0103002
	N male-N female, straight		MX0103003
	N male-N female, right angle		MX0103004
	DIN 7-16 male-DIN 7-16 male, straight		MX0103005
	DIN 7-16 female-DIN 7-16 female, straight		MX0103006
	DIN 7-16 male-DIN 7-16 female, straight		MX0103007
	DIN 7-16 male-DIN 7-16 female, right angle		MX0103008
	N male, straight-DIN 7-16 male		MX0103009
	N male, straight-DIN 7-16 female		MX0103010
	N female, straight-DIN 7-16 male		MX0103011
	N female, straight-DIN 7-16 female		MX0103012