**MAXDAO**

# Cat5e cable assembly, with two RJ45 connectors, 75meters

- **4 solid FTP twisted pair**
- **Meets all Cat5e standards**
- **Perfect for running in a network**
- **RoHS certified**

## Product Classification

| | |
|---|---|
| Material Code | 6002599 |
| Part Number | - |
| Status | Active |
| Detail Description | Cat5e cable assembly, 4 pair, FTP, 24 AWG solid, black PE jacket, 75meters, with two RJ45 connector |

## General Specifications

| | |
|---|---|
| Cable Type | FTP |
| No. Of Conductor | 4 Pair |
| Conductor Gauge | 24 AWG |
| Conductor Type | Solid |
| Jacket Material | PE |
| Jacket Color | Black |
| Connector Type | RJ45 |

## Dimensions

| | |
|---|---|
| Conductor Structure | 1/0.51±0.008 |
| Insulation Diameter | 0.98 mm \| 0.04 in |
| Jacket Diameter | 6.0 mm \| 0.24 in |
| Length | 75 Meters |

## Electrical Specifications

| | |
|---|---|
| Insulation Resistance | ≥ 5000 MΩ，at 20℃ |
| Dielectric Test | 1000V DC /1 min, no breakdown |
| Rated Voltage | 300 V |

## Environmental Specifications

| | |
|---|---|
| Operating Temperature | -20 °C to +60 °C |

## Packaging and Weights

**MAXDAO**

| | |
|---|---|
| Height, packed | 100 mm \| 3.94 in |
| Width, packed | 300 mm \| 11.81 in |
| Length, packed | 300 mm \| 11.81 in |
| Include | Two RJ45 connector |
| Packaging Quantity and UOM | 1 Kit |
| Weight, gross | 2.62 kg \| 5.77 lb |

## Certifications and Compliance

| | |
|---|---|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| ROHS | Compliant |