


Copper Lug, AWG 2/0#, one hole 3/8", standard barrel, with inspection window

- Copper cable lugs are designed for connecting copper cables, coils and Bus-bars.
- Copper Tube Terminals between 6mm² & 800mm² have bell entry to ensure easy entry even for flexible conductors.
- Incorporates inspection window to check the correct cable positioning.
- "colour code" help choose the right connector, the colour name is also printed in order to avoid problems for those who are colour-blind.
- Narrow tongue design for limited space applications.



Product Classification		
Material Code	6004338	
Part Number	-	
Detail Description	Copper Lug, AWG 2/0#, one hole 3/8", standard barrel, with inspection window	
General Specifications		
Color Code	Pink	
Material	Copper	
Tongue Type	Narrow	
Tongue Angle	Straight	
Surface	Tin-plated	
Inspection Window	With inspection window	

Dimensions



Electrical Specifications		
Outer diameter (OD)	0.56 in 14.2 mm	
Inner diameter (ID)	0.45 in 11.2 mm	
Overall length (L)	2.75 in 69.9 mm	
Barrel length (B)	1.38 in 35.1 mm	
Tang Width (C)	0.63 in 15.8 mm	
Bolt Size	3/8 in 10.2 mm	

For more information, please visit: www.maxdao.com

Rating - Maximum Voltage 35KV





DOC#ITM-04-01, Version: A/2, Updated: 02/28/2023



Environmental Specifications	
Operating Temperature	-40 °C to +90°C (-40 °F to +212 °F)
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)
Packaging and Weights	
Included	Lug
Packaging Quantity and UOM	1 pcs
Piece Weight	0.073 lb 0.033 kg
Certifications and Certificated	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL&CSA	Compliant