## MAXDAO

## Stainless Steel Banding, 1/2 in x100 ft

- Easy and quick installation,
- Robust design & material for outdoor use

6007644
-
Active
Stainless steel banding, 1/2 in x100 ft
Stainless steel 201
Silver
Banding tool
100 ft   30 m
0.5 in   12.7 mm
3.071 in   78 mm
-40 °C to +85 °C (-40 °F to +185 °F)
2000 lb
≥72 hours, base on IEC 60068 -2-11
1.378 in   35 mm
11.811 in   300 mm
19.685 in   500 mm
1 roll
5.379 lb   2.44kg

Certifications and Compliance

For more information, please visit: www.maxdao.com

## ©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Mar 3, 2023 Public Page 1 of 2





DATASHEET

ISO 9001:2015

ROHS

Designed, manufactured and/or distributed under this quality management system Compliant

MAXDAO

For more information, please visit: www.maxdao.com

 $\boxtimes$ (in

©Copyright 2023 Maxdao Inc. All rights reserved. The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Mar 3, 2023 Public

Page 2 of 2