

Strain Relief Grip, Deluxe Cord,PG29,Straight Male,Cable Range 0.56-0.69 in, SS304

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- UL, CE certified



Product Classification

Material Number	6007980
Part Number	-
Detail Description	Strain Relief Grip, Deluxe Cord,PG29,Straight Male,Cable Range 0.56-0.69 in, SS304

Details

Cable Range	0.56-0.69 in 14.2-17.5 mm
Thread Size	PG29
Mesh Length	7.5 in 190.5 mm
Approximate Break Strength	550 lbs 249 kg
Mesh Material	Stainless Steel
Ring Material	Aluminum Alloy

Performance

Flammability	UL 94HB & UL 94V-2
Operating Temperatures	-34 °C to +115 °C (-30 °F to +240 °F)
Wet Locations	Suitable for use in wet locations when used with a listed sealing ring between box and fitting

Packaging and Weights

UOM	1 pcs
Packaging	Bag
Weight, gross	0.68 lb 0.28 kg

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant



CE	Compliant
UL	Compliant

