

Grounding Kit, Universal Type, 1/4"-1-5/8", 0.6 Meter, Copper-clad aluminum grounding cable

- Easy and quick installation
- Low contact transition resistance of maximum 10mΩ
- Operation Temperature -40~70 °C
- Waterproof IP68



Product Classification	
Item Number	6009314
Part Number	-
Detail Description	Grounding Kit, universal type, for 1/4"-1-5/8" cable, 0.6 Meter, installation accessories including
General Specifications	
Bonding Conductor Material	Copper-clad aluminum
Bonding Conductor Wire Size	16mm ²
Grounding Strap Material	Copper, Tin Plated
Lug Type	One-hole lug
Screw Material	Stainless Steel
Flat washer Material	Stainless Steel
Spring washer Material	Stainless Steel
Nut Material	Stainless Steel
PVC tape Material	PVC
Butyl Rubber Tape Material	Butyl
Dimensions	
Bonding Conductor Length	0.6 m 2 feet
Lug Hole Size	M8
Screw Size	M8x25 mm
Suitable Cable	1/4"-1-5/8"
Environmental Specifications	
Operating Temperature	-40°C to +70 °C (-40 °F to +158 °F)
Weatherproofing Method	Butyl and electric tape
Electrical Specifications	
Contact Transition Resistance	Maximum 10mΩ



Packaging and Weights	
Height, Packed	320 mm 12.60 in
Width, Packed	220 mm 8.66 in
Included	Grounding kit Hardware Lug One roll of PVC tape One roll of butyl rubber tape One Braided ground strap
UOM	Kit
Packaging	Bag
Weight, Gross	0.194 kg 0.427 lbs
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

