


Copper Lug, AWG 1/0#, two hole 1/4", hole spacing 5/8" , with inspection window, pink

- Copper cable lugs are designed for connecting copper cables, coils and Bus-bars
- Copper Tube Terminals between 6mm² & 800mm² have bell entry to ensure easy entry even for flexible conductors.
- Incorporates inspection window to check the correct cable positioning.
- The barrel length has been designed to allow easy and accurate positioning of the dies during the crimping operation.
- "colour code" help choose the right connector, the colour name is also printed in order to avoid problems for those who are colour-blind.




Product Classification

Item Number	6009364
Part Number	-
Detail Description	Copper Lug, AWG 1/0#, two hole 1/4", hole spacing 5/8" , with inspection window, pink

General Specifications

Colour Code	Pink
Material	Copper
Tongue Type	Standard
Tongue Angle	Straight
Surface	Tin-plated
Inspection Window	With inspection window

Dimensions



Bolt Size	1/4 in 6.9 mm
Hole Spacing (H)	5/8 in 16.0 mm
Tang Width (C)	0.57 in 14.5 mm
Barrel length (B)	0.91 in 23.1 mm
Overall length (L)	2.66 in 67.6 mm

Inner diameter (ID)	0.39 in 9.9 mm
Outer diameter(OD)	0.52 in 13.2 mm
Electrical Specifications	
Rating - Maximum Voltage	35KV
Environmental Specifications	
Operating Temperature	-40 °C to +90°C (-40 °F to +212 °F)
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)
Packaging and Weights	
Included	Lug
Packaging Quantity and UOM	1 pcs
Piece Weight	0.11 lb 0.05 kg
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL	Compliant

