

Grounding Kit, High Speed Type, 1/4", 0.8 Meter

- Easy and quick installation
- Low contact transition resistance of maximum 10mΩ
- Operation Temperature -40~70 °C
- Waterproof IP68



Product Classification

|                    |  |
|--------------------|--|
| Item Number        | 6009387  |
| Part Number        | -  |
| Detail Description | Grounding kit, high speed type, for 1/4" cable, 0.8 Meter, installation accessories included |

General Specifications

|                             |                             |
|-----------------------------|-----------------------------|
| Bonding Conductor Material  | Copper Clad Aluminum        |
| Bonding Conductor Wire Size | AWG6                        |
| Grounding Strap Material    | Stainless Steel Coated EPDM |
| Lug Type                    | One-hole lug                |
| Screw Material              | Stainless Steel             |
| Flat washer Material        | Stainless Steel             |
| Spring washer Material      | Stainless Steel             |
| Nut Material                | Stainless Steel             |

Dimensions

|                          |                   |
|--------------------------|-------------------|
| Bonding Conductor Length | 0.8 m   2.68 feet |
| Lug Hole Size            | M8                |
| Screw Size               | M8x25 mm          |
| Suitable Cable           | 1/4"              |

Environmental Specifications

|                       |                                     |
|-----------------------|-------------------------------------|
| Operating Temperature | -40°C to +70 °C (-40 °F to +158 °F) |
| Waterproof            | IP68, base on IEC60529              |

Electrical Specifications

|                               |              |
|-------------------------------|--------------|
| Contact Transition Resistance | Maximum 10mΩ |
|-------------------------------|--------------|

Packaging and Weights

|                |                  |
|----------------|------------------|
| Height, Packed | 200 mm   7.87 in |
| Width, Packed  | 200 mm   7.87 in |

For more information, please visit:  
www.maxdao.com



©Maxdao Inc. All rights reserved.  
The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.  
Revised: May 14, 2025  
Public

|                                      |  |
|--------------------------------------|--|
| Included                             | Grounding kit   Hardware   Release Paper                                       |
| UOM                                  | Kit  |
| Packaging                            | Bag  |
| Weight, Gross                        | 0.181 kg   0.399 lbs   |
| <b>Certifications and Compliance</b> |  |
| ISO 9001:2015                        | Designed, manufactured and/or distributed under this quality management system |
| RoHS                                 | Compliant  |

