

## Strain Relief Grip, Deluxe Cord, M32, Straight Male, Cable Range 0.875-1.000"

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- UL, CE certified



| Product Classification        |  |
|-------------------------------|--|
| Item Number                   | 6009388  |
| Part Number                   | -  |
| Detail Description            | Strain Relief Grip, Deluxe Cord, M32, Straight Male, Cable<br>Range 0.875-1.000" |
| Details                       |  |
| Cable Range                   | 0.875-1.000 in   22.3-25.4 mm  |
| Thread Size                   | M32  |
| Mesh Length                   | 9.0 in   228.6 mm  |
| Approximate Break Strength    | 800 lbs   362 kg   |
| Mesh Material                 | Stainless Steel  |
| Ring Material                 | Aluminum Alloy   |
| Performance                   |  |
| Flammability                  | UL 94HB & UL 94V-2   |
| Operating Temperatures        | -34 °C to +115 °C (-30 °F to +240 °F)  |
| Packaging and Weights         |  |
| UOM                           | 1 pcs  |
| Packaging                     | Bag  |
| Weight, gross                 | 0.89 lb   0.40 kg  |
| Certifications and Compliance |  |
| ISO 9001:2015                 | Designed, manufactured and/or distributed under this quality management system   |
| RoHS                          | Compliant  |
| CE                            | Compliant  |
|                               |  |

Х

## ©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Aug 30, 2024 Public DATASHEET

UL

Compliant



For more information, please visit: www.maxdao.com

 $\square$ in

©Maxdao Inc. All rights reserved. The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Aug 30, 2024 Public

Page 2 of 2