

Cold Shrink Tube, ϕ30x110mm, Black

- Easy and quick installation
- Manufactured from silicone rubber
- Suitable for a wide range of cable sizes
- No special tools or training required for installation
- Offering good mechanical, insulation and sealing protection



Product Classification

Item Number	6009415
Part Number	-
Detail Description	Cold shrink tube, ϕ30x110mm, black

General Specifications

Material	Silicone
Cable type	Corrugated Elliptical Waveguide Smoothwall
Cable Range	Φ8-25 mm 0.315-0.984 in
Color	Black
Mastic(Y/N)	N
Shrink Ratio	4:1

Dimensions

Length Before Shrink	110 mm 4.331 in
Length After Shrink	131 mm 5.157 in
Inner Diameter Before Shrink(ID)	30 mm 1.181 in
Inner Diameter After Shrink(ID)	7 mm 0.275 in
Thickness After Shrink	3.1 mm 0.122 in

Environmental Specifications

Operating Temperature	-60 °C to +90 °C (-76 °F to +194 °F)
Weatherproof Resistance	IP68, based on ISO20653:2013
UV Resistance	≥1000 hours, base on ASTM G154-16

Packaging and Weights

Height, Packed	260 mm 10.23 in
Width, Packed	70 mm 2.75 in
UOM	1 Pcs
Packaging	Bag

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.
The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.
Revised: Jun 10, 2025
Public

Weight, Gross	0.040 kg 0.088 lbs
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

