

Continuously Adjustable Attenuator, N Female To N Female

- 0 to 10dB Variable Attenuator
- Rotary Dial Design For Continuous Adjustment
- Frequency Range From 2GHz to 4GHz
- N Female Connector Design



Product Classification	
Item Number	6009432
Part Number	-
Detail Description	0 to 10dB Continously adjustable attenuator, N Female To N Female
General Specifications	
Bonding Material	Aluminum
Connector Type	N Female To N Female
Dimensions	
Length	189.5 mm 7.46 in
Width	102.0 mm 4.01 in
Height	31.5 mm 1.24 in
Environmental Specifications	
Operating Temperature	-20°C to +55 °C (-4 °F to +131 °F)
Electrical Specifications	
Frequency Range	2GHz to 4GHz
Impedance	50Ω
Attenuation Value	0 to 10dB
VSWR	≤1.5:1
Insertion Loss	≤0.5dB
Input Power	100W
Packaging and Weights	
Height, Packed	370 mm 14.56 in
Width, Packed	210 mm 8.26 in
UOM	Pcs
Packaging	Bag
Weight, Gross	1.21 kg 2.67 lbs



Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

