

Grounding Kit, Tinned Universal Type, 1/2"-3", 1.5 Meter, With Installation Guide

- Easy and quick installation
- Low contact transition resistance of maximum 10mΩ
- Operation Temperature -40~70 °C
- Waterproof IP68



Product Classification	
Item Number	6009436
Part Number	-
Detail Description	Grounding kit, tinned universal type, for 1/2"-3" cable, 1.5 meter, installation accessories including
General Specifications	
Bonding Conductor Material	Copper
Bonding Conductor Wire Size	AWG 6
Grounding Strap Material	Copper, Tin Plated
Lug Type	Two-hole lug
Screw Material	Stainless Steel
Flat washer Material	Stainless Steel
Spring washer Material	Stainless Steel
Nut Material	Stainless Steel
PVC tape Material	PVC
Butyl Rubber Tape Material	Butyl
Dimensions	
Bonding Conductor Length	1.5 m 5 feet
Lug Hole Size	3/8"
Screw Size	3/8"x1"
Suitable Cable	1/2"-3"
Environmental Specifications	
Operating Temperature	-40°C to +70 °C (-40 °F to +158 °F)
Weatherproofing Method	Butyl and electric tape
Electrical Specifications	
Contact Transition Resistance	Maximum 10mΩ
Packaging and Weights	



Height, Packed	370 mm 14.56 in
Width, Packed	210 mm 8.26 in
Included	Grounding kit Hardware Lug One roll of PVC tape One roll of butyl rubber tape Installation guide
UOM	Pcs
Packaging	Bag
Weight, Gross	0.587 kg 1.294 lbs
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

