


90° Copper Lug, AWG 6#, two hole 10#, hole spacing 5/8", short barrel, with inspection window

- Copper cable lugs are designed for connecting copper cables, coils and Bus-bars
- Copper Tube Terminals between 6mm² & 800mm² have bell entry to ensure easy entry even for flexible conductors.
- Incorporates inspection window to check the correct cable positioning
- 90 degree short barrel for limited space applications.




Product Classification

Item Number	6004459
Part Number	-
Detail Description	90° Copper Lug, AWG 6#, two hole 10#, hole spacing 5/8", short barrel, with inspection window

General Specifications

Material	Copper
Tongue Type	Standard
Tongue Angle	90 degree
Surface	Tin-plated
Inspection Window	With inspection window

Dimensions



Bolt Size	0.20 in 5.2 mm
Hole Spacing (H)	5/8 in 16.0 mm
Tang Width (C)	0.42 in 11.5 mm
Barrel length (B)	0.54 in 13.5 mm
Overall length (L)	1.57 in 40.0 mm
Inner diameter (ID)	0.22 in 5.6 mm
Outer diameter (OD)	0.31 in 7.9 mm

Electrical Specifications

Rating - Maximum Voltage	35KV
--------------------------	------

Environmental Specifications

Operating Temperature	-40 °C to +90°C (-40 °F to +212 °F)
-----------------------	-------------------------------------

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Feb 28, 2023

Public

Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)
---------------------	--------------------------------------

Packaging and Weights

Included	Lug
Packaging Quantity and UOM	1 pcs
Piece Weight	0.026 lb 0.012 kg

Certifications

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL	Compliant

