

Liquid Tight Grip,NPT 2-1/2",90° Male,Galvanized Steel

- Used to connect liquid tight conduit to electrical enclosures to help prevent conduit pullout.
- Liquid tight grips are recommended in the wiring of motors and any electrical enclosure where liquid tight conduits subject to motion or strain.
- Insulated throat provides protection upon flexing,temperature change and wire entry/exit.
- UL&CE certified



Product Classification	
Item Number	6009597
Part Number	-
Detail Description	Liquid Tight Grip,NPT 2-1/2",90° Male,Galvanized Steel
Details	
Thread Size	NPT 2-1/2
Mesh Length	11.25 in 285.8 mm
Approximate Break Strength	1100 lbs 498 kg
Mesh Material	Galvanized Steel
Connector Material	Zinc Plated Malleable Iron
Performance	
Flammability	UL 94HB & UL 94V-2
Operating Temperatures	-34 °C to +115 °C (-30 °F to +240 °F)
Packaging and Weights	
UOM	1 pcs
Packaging	Bag
Weight, gross	3.3 lb 1.5 kg
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
CE	Compliant
UL	Compliant

