

Twine Type Grounding Kit ,for cable 1/4"-1-5/8",0.5m

- Easy and quick installation
- Low contact transition resistance of maximum 10mΩ
- Suitable for screen diameter of cable OD 1/4"-1-5/8"
- Operation Temperature -40~70 °C
- Waterproof IP68



Product Classification

Material Number	6003350
Status	Active
Detail Description	Twine Type Grounding Kit,for cable 1/4"-1-5/8",0.5m,installation accessories including

General Specifications

Bonding Conductor Material	Copper,Tin Plated
Bonding Conductor Wire Size	AWG6
Grounding Strap Material	Copper,Tin Plated
Lug Type	One-hole lug
Screw Material	Stainless Steel
Flat washer Material	Stainless Steel
Spring washer Material	Stainless Steel
Nut Material	Stainless Steel
PVC tape Material	PVC
Butyl Rubber Tape Material	Butyl

Dimensions

Bonding Conductor Length	0.5 m 19.6 in
Lug Hole Size	M8
Screw Size	M8x25

Electrical Specifications

Contact Transition Resistance	Maximum 10mΩ
-------------------------------	--------------

Packaging and Weights

Height, packed	180 mm 7.0 in
Width, packed	310 mm 12.2 in

Length, packed	400 mm 15.75 in
Included	Grounding kit M8x25 screw M8 spring washer M8 flat washer M8 nut One roll of 6m PVC tape One roll of 0.6m butyl rubber Tape
UOM	1 Kit
Packaging	Bag
Weight, gross	0.230 kg 0.507 lb

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant

