

Grounding Kit, Standard Type, 5-26mm, 2 Meter

- Easy and quick installation
- Low contact transition resistance of maximum 10mΩ
- Operation temperature -40~70 °C
- Waterproof IP68



Product Classification	
Item Number	6009567
Part Number	-
Detail Description	Grounding kit, standard type, for 5-26mm OD cable, 2 meter, installation accessories included
General Specifications	
Bonding Conductor Material	Copper
Bonding Conductor Wire Size	AWG 6
Braided Ground Strap Material	Copper, Tin-plated
Lug Type	One-hole lug
Screw Material	Stainless Steel
Flat washer Material	Stainless Steel
Spring washer Material	Stainless Steel
Nut Material	Stainless Steel
Tape Material	PVC & Butyl
Dimensions	
Bonding Conductor Length	2 m 78.74 in
Lug Hole Size	M8
Screw Size	M8x25
Suitable Cable OD	5-26mm
Environmental Specifications	
Operating Temperature	-40°C to +70 °C (-40 °F to +158 °F)
Weatherproofing Method	Butyl and electric tape
Electrical Specifications	
Contact Transition Resistance	Maximum 10mΩ
Packaging and Weights	
Height, Packed	320 mm 12.60 in



Width, Packed	220 mm 8.66 in
Included	Grounding kit Hardware Lug One roll of PVC tape One roll of butyl rubber tape Silicone grease
UOM	Kit
Packaging	Bag
Weight, Gross	0.685 kg 1.510 lbs
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

