

Hook Cable Clamp, E Type, 4x12-22mm

- Easy and quick installation
- Robust design & material for outdoor use
- Operation Temperature -40~85 °C
- Hooking on section 40×22, flat and round 3-12 mm



| Product Classification | |
|-------------------------------------|---|
| Item Number | 6009571 |
| Part Number | - |
| Detail Description | Hook Cable Clamp for 4x12-22mm OD cable, hooking on section 40×22, flat and round 3-12 mm |
| General Specifications | |
| Metal Material | Stainless steel 304 |
| Block Material | PA6 |
| Block Color | Black |
| Cables Per Hanger | 4 x 12-22 mm |
| Dimensions | |
| Height | 230.0 mm 9.06 in |
| Width | 30.4 mm 1.20 in |
| Length | 41.5 mm 1.63 in |
| Compatible Cable Jacket OD, maximum | 22.0 mm 0.87 in |
| Compatible Cable Jacket OD, minimum | 12.0 mm 0.47 in |
| Environmental Specifications | |
| Operating Temperature | -40 °C to +85 °C (-40 °F to +185 °F) |
| Corrosion Resistance | \geqslant 96 hours in salt spray chamber, base on ISO 9227:2017 |
| UV Resistance | ≥720 hours, base on ISO4892.3-1994 |
| Vibration Test | ≥6 hours,base on IEC 60068-2-6-2007 |
| Packaging and Weights | |
| Height, Packed | 300 mm 11.81 in |
| Width, Packed | 120 mm 4.72 in |
| UOM | 1 Pcs |

For more information, please visit:

www.maxdao.com







| Packaging | Bag |
|-------------------------------|--|
| Weight, Gross | 0.165 kg 0.363 lbs |
| Certifications and Compliance | |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |