

ΜΑΧΡΔΟ

90° Copper Lug, AWG4#, two hole 1/4", hole spacing 5/8", long barrel, with inspection window, Gray

- Copper cable lugs are designed for connecting copper cables, coils and Bus-bars
- Copper Tube Terminals between 6mm2 & 800mm2 have bell entry to ensure easy entry even for flexible
- Incorporates inspection window to check the correct cable positioning.
- The barrel length has been designed to allow easy and accurate positioning of the dies during the crimping operation.
- "colour code" help choose the right connector, the colour name is also printed in order to avoid problems for those who are colour-blind.



Product Classification	
Item Number	6009602
Part Number	-
Detail Description	90° Copper Lug,AWG4#,two hole 1/4",hole spacing 5/8",long barrel,with inspection window, Gray
General Specifications	
Colour Code	Gray
Material	Copper
Tongue Type	Standard
Tongue Angle	90 degree
Surface	Tin-plated
Inspection Window	With inspection window
Dimensions	BOLT SIZE I I





Bolt Size	1/4 in 6.9 mm
Hole Spacing (H)	0.63 in 16.0 mm
Tang Width (C)	0.55 in 14.0 mm
Barrel length (B)	1.12 in 28.5 mm

For more information, please visit: www.maxdao.com





Overall length (L)	1.74 in 44.2 mm
Inner diameter (ID)	0.28 in 7.2 mm
Outer diameter(OD)	0.38 in 9.7 mm
Electrical Specifications	
Rating - Maximum Voltage	35KV
Environmental Specifications	
Operating Temperature	-40 °C to +90°C (-40 °F to +212 °F)
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)
Packaging and Weights	
Included	Lug
Packaging Quantity and UOM	1 pcs
Piece Weight	0.08 lb 0.04 kg
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL	Compliant

