

Cold Shrink Tube, $\phi 20 \times 190$ mm, Black

- Manufactured by silicone rubber
- Excellent for outdoor use & indoor use
- Excellent weatherproof performance



Product Classification

Material Number	6005727
Part Number	-
Status	Active
Detail description	Cold shrink tube, $\phi 20 \times 190$ mm, Black

General Specifications

Material	Silicone rubber
Cable type	Corrugated Elliptical Waveguide Smoothwall
Cable size	$\phi 6$ mm- $\phi 16$ mm
Color	Black
Mastic(Y/N)	N
Shrink ratio	4:1

Dimensions

Length before shrink	190 mm 7.48 in
Length after shrink	210 mm 8.27 in
Inner diameter before shrink(ID)	20 mm 0.78 in
Inner diameter after shrink(ID)	5 mm 0.20 in
Thickness after shrink	3 mm 0.12 in

Environmental Specifications

Operating temperature	-40°C to +85°C (-40°F to +185°F)
Weatherproof resistance	IP67, based on ISO20653:2013
UV resistance	≥ 720 Hours, based on ISO 4892-3

Packaging and Weights

Bag width	220 mm 8.66 in
Bag length	320 mm 12.60 in

Packaging quantity and UOM	1 pcs
Weight gross	0.0432 kg 0.095 lb

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant

