TEMPLATE# ITM0401 VERSION A/8 DATE 08/20/2024



Circular Connector, Straight Plug, 4 Contacts, Solder Pin

- Environmental sealing is achieved with the grommet and clamp design
- Pin and socket contacts are machined from low loss copper alloy and gold plated to eliminate contact corrosion
- IP67



Product Classification		
Item Number	6009607	
Part Number	MS3116F8-4P	
Detail Description	4 Position Circular Connector Plug, Male Pins Solder Cup	
General Specifications		
Number of Positions	4 Position	
Shell Size - Insert	8-4	
Contact Material	Copper	
Contact Finish	Gold-plating	
Shell Material	Aluminum	
Shell Finish	Olive Drab Cadmium	
Mounting Type	Free Hanging (In-Line)	
Termination	Solder Cup	
Fastening Type	Bayonet Lock	
Dimensions		
Height	18.7 mm 0.74 in	
Width	19.1 mm 0.75 in	
Length (Max)	48.7 mm 1.92 in	
Electrical Specifications		
Current Rating	7.5A	
Voltage Rating	1200V	
Contact Resistance	≤5mΩ	
Insulation Resistance	≥5000mΩ	
Environmental Specifications		
Operating Temperature	-55 °C to +125 °C	

For more information, please visit: www.maxdao.com







Lifetime	≥500 times
IP Rate	IP67
Packaging and Weights	
UOM	1 Pcs
Packaging	Bag
Weight, Gross	0.016 kg 0.035 lbs
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

