


Feeder Cable Clamp, 6 holes, 3x4.5-7mm+3x9-14mm, Q235 Plated Dacromet

- **Easy and quick installation**
- **Robust design & material for outdoor use**
- **Operation Temperature -40~85 °C**

**Classification**

Item Number	6002432
Part number	-
Detail Description	Feeder cable clamp, for 3x4.5-7mm OD cable and 3x9-14mm OD cable, Q235 plated dacromet

General Specifications

Metal Material	Steel Q235
Surface Treatment	Plated Dacromet
Block Material	PP
Block Color	Black
Rubber Material	EPDM
Rubber Color	Black
Mounting	M8 Hardware
Cables Per Hanger	6

Dimensions

Height	36.0 mm 1.42 in
Width	40.0 mm 1.57 in
Length	190.0 mm 7.48 in
Threaded Rod Length	120.0 mm 4.72 in
Compatible Cable 1 OD, maximum	7.0 mm 0.276 in
Compatible Cable 1 OD, minimum	4.5 mm 0.177 in
Compatible Cable 2 OD, maximum	14.0 mm 0.67 in
Compatible Cable 2 OD, minimum	9.0 mm 0.354 in

Environmental Specifications

Operating Temperature	-40°C to +85°C(-40°F to +185°F)
Environmental Strength Capability	Double Cable Weight
UV Resistance	≥720 Hours, base on ISO4892.3-1994

Packaging and Weights

Height, Packed	320 mm 12.60 in
Width, Packed	220 mm 8.66 in
UOM	1 Pcs
Packaging	Bag
Weight, Gross	0.228 kg 0.503 lbs

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant