

Hook Cable Clamp, M Type, 12 holes, 12x11-21mm

- Easy and quick installation
- Robust design & material for outdoor use
- Operation Temperature -40~85 °C
- Hooking on round ø8-25mm and flat 3-25mm



| Product Classification            |                                                                                     |
|-----------------------------------|-------------------------------------------------------------------------------------|
| Item Number                       | 6003373                                                                             |
| Part Number                       | -                                                                                   |
| Detail Description                | Hook cable clamp, for 12x11-21mm OD cable, hooking on round ø8-25mm and flat 3-25mm |
| General Specifications            |                                                                                     |
| Metal Material                    | Stainless Steel 304                                                                 |
| Block Material                    | PA6                                                                                 |
| Block Color                       | Black                                                                               |
| Cables Per Hanger                 | 12                                                                                  |
| Dimensions                        |                                                                                     |
| Height                            | 355 mm   13.98 in                                                                   |
| Width                             | 45.0 mm   1.77 in                                                                   |
| Length                            | 56.7 mm   2.23 in                                                                   |
| Compatible Cable OD, maximum      | 21.0 mm   0.83 in                                                                   |
| Compatible Cable OD, minimum      | 11.0 mm   0.43 in                                                                   |
| Environmental Specifications      |                                                                                     |
| Operating Temperature             | -40°C to +85°C(-40°F to+185°F)                                                      |
| Environmental Strength Capability | Double Cable Weight                                                                 |
| UV Resistance                     | ≥720 Hours, base on ISO4892.3-1994                                                  |
| Vibration Test                    | ≥6 Hours,base on IEC 60068-2-6-2007                                                 |
| Packaging and Weights             |                                                                                     |
| Height, Packed                    | 370 mm   14.57 in                                                                   |
| Width, Packed                     | 210 mm   8.27 in                                                                    |
| UOM                               | 1 Pcs                                                                               |
| Packaging                         | Bag                                                                                 |



|                                      |                                                                                |
|--------------------------------------|--------------------------------------------------------------------------------|
| Weight, Gross                        | 0.395 kg   0.871 lbs                                                           |
| <b>Certifications and Compliance</b> |                                                                                |
| ISO 9001:2015                        | Designed, manufactured and/or distributed under this quality management system |
| RoHS                                 | Compliant                                                                      |

