

Rotary Waveguide Cable Clamp, Rubber Lining Hole 25x15mm, For R140 Waveguide

- Easy and quick installation
- Robust design & material for outdoor use
- Universal fixing design on pole
- Operation Temperature -40~85 °C



|                               |  |
|-------------------------------|--|
| Classification                |  |
| Item Number                   | 6003620  |
| Part number                   | -  |
| Detail Description            | Rotary waveguide cable clamp, for R140 rectangular waveguide |
| General Specifications        |  |
| Metal Material                | Stainless Steel 304  |
| Metal Color                   | Natural  |
| Rubber Material               | Natural Rubber   |
| Rubber Color                  | Black  |
| Fit Mounting Pole OD          | 40-150 mm   1.57- 5.91 in                                    |
| Waveguide Size                | WR62   R140  |
| Dimensions                    |  |
| Threaded Rod Length           | 400.0 mm   15.75 in  |
| Rubber Lining Hole            | 25.0x15.0 mm   0.98x0.59 in                                  |
| Environmental Specifications  |  |
| Operating Temperature         | -40°C to +85°C(-40°F to+185°F)                               |
| UV Resistance                 | ≥720 Hours, base on ISO4892.3-1994                           |
| Salt Spray                    | ≥720 Hours, base on IEC60028-2-11                            |
| Packaging and Weights         |  |
| Height, Packed                | 600 mm   23.62 in  |
| Width, Packed                 | 200 mm   7.87 in   |
| UOM                           | 1 Pcs  |
| Packaging                     | Bag  |
| Weight, Gross                 | 0.386 kg   0.851 lbs   |
| Certifications and Compliance |  |
| ISO 9001:2015                 | Designed, manufactured and/or distributed under this         |



|      |                           |
|------|---------------------------|
|      | quality management system |
| RoHS | Compliant                 |

