

Rotary Waveguide Cable Clamp, Rubber Lining Hole 14x10mm, For R320 Waveguide

- Easy and quick installation
- Robust design & material for outdoor use
- Universal fixing design on pole
- Operation Temperature -40~85 °C



Classification		
Item Number	6003641	
Part number	-	
Detail Description	Rotary waveguide cable clamp, for R320 rectangular waveguide	
General Specifications		
Metal Material	Stainless Steel 304	
Metal Color	Natural	
Rubber Material	Natural Rubber	
Rubber Color	Black	
Fit Mounting Pole OD	40-150 mm 1.57- 5.91 in	
Waveguide Size	WR28 WR22 R320 R400	
Dimensions		
Threaded Rod Length	400.0 mm 15.75 in	
Rubber Lining Hole	14.0x10.0 mm 0.55x0.39 in	
Environmental Specifications		
Operating Temperature	-40°C to +85°C(-40°F to+185°F)	
UV Resistance	≥720 Hours, base on ISO4892.3-1994	
Salt Spray	≥720 Hours, base on IEC60028-2-11	
Packaging and Weights		
Height, Packed	600 mm 23.62 in	
Width, Packed	200 mm 7.87 in	
UOM	1 Pcs	
Packaging	Вад	
Weight, Gross	0.390 kg 0.860 lbs	
Certifications and Compliance		
ISO 9001:2015	Designed, manufactured and/or distributed under this	

For more information, please visit: www.maxdao.com





	quality management system
RoHS	Compliant



