


Feeder Cable Clamp, 1 hole, 1x3/8"

- Easy and quick installation
- Robust design & material for outdoor use
- Operation Temperature -40~85 °C



|                                   |                                              |
|-----------------------------------|----------------------------------------------|
| Classification                    |                                              |
| Item Number                       | 6003806                                      |
| Part number                       | -                                            |
| Detail Description                | Feeder cable clamp, for 1x3/8" coaxial cable |
| General Specifications            |                                              |
| Metal Material                    | Stainless Steel 304                          |
| Metal Color                       | Natural                                      |
| Block Material                    | PP                                           |
| Block Color                       | Black                                        |
| Mounting                          | M8 Hardware                                  |
| Cables Per Hanger                 | 1                                            |
| Dimensions                        |                                              |
| Height                            | 34.5 mm   1.36 in                            |
| Width                             | 33.0 mm   1.30 in                            |
| Length                            | 130.0 mm   5.12 in                           |
| Threaded Rod Length               | 60.0 mm   2.36 in                            |
| Compatible Cable OD, maximum      | 11.0 mm   0.43 in                            |
| Compatible Cable OD, minimum      | 10.0 mm   0.39 in                            |
| Environmental Specifications      |                                              |
| Operating Temperature             | -40°C to +85°C(-40°F to+185°F)               |
| Environmental Strength Capability | Double Cable Weight                          |
| UV Resistance                     | ≥720 Hours, base on ISO4892.3-1994           |
| Packaging and Weights             |                                              |
| Height, Packed                    | 200 mm   7.87 in                             |
| Width, Packed                     | 200 mm   7.87 in                             |
| UOM                               | 1 Pcs                                        |



|                                      |                                                                                |
|--------------------------------------|--------------------------------------------------------------------------------|
| Packaging                            | Bag                                                                            |
| Weight, Gross                        | 0.135 kg   0.297 lbs                                                           |
| <b>Certifications and Compliance</b> |                                                                                |
| ISO 9001:2015                        | Designed, manufactured and/or distributed under this quality management system |
| RoHS                                 | Compliant                                                                      |

