

Feeder Cable Clamp, 4 holes, 4x1/2", Salt Spray 720 hours

- Easy and quick installation
- Robust design & material for outdoor use
- Operation Temperature -40~85 °C



Classification	
Item Number	6003886
Part number	-
Detail Description	Feeder cable clamp, for 4x1/2" coaxial cable, salt spray 720 hours
General Specifications	
Metal Material	Stainless Steel 304
Surface Treatment	Passivation
Block Material	PP
Block Color	Black
Mounting	M8 Hardware
Cables Per Hanger	4
Dimensions	
Height	36.5 mm 1.44 in
Width	58.8 mm 2.31 in
Length	160.0 mm 6.30 in
Threaded Rod Length	90.0 mm 3.54 in
Compatible Cable OD, maximum	17.0 mm 0.67 in
Compatible Cable OD, minimum	16.0 mm 0.63 in
Environmental Specifications	
Operating Temperature	-40°C to +85°C(-40°F to+185°F)
Environmental Strength Capability	Double Cable Weight
UV Resistance	≥720 Hours, base on ISO4892.3-1994
Salt Spray	≥720 Hours, base on IEC60028-2-11
Packaging and Weights	
Height, Packed	320 mm 12.60 in





Width, Packed	220 mm 8.66 in
UOM	1 Pcs
Packaging	Bag
Weight, Gross	0.181 kg 0.399 lbs
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant



www.maxdao.com

For more information, please visit: