

Hook Cable Clamp, M Type, 18 holes, 12x5-7mm+6x10-22mm

- Easy and quick installation
- Robust design & material for outdoor use
- Operation Temperature -40~85 °C
- Hooking on round ø8-25mm and flat 3-25mm



Product Classification

| | |
|--------------------|---|
| Item Number | 6004387 |
| Part Number | - |
| Detail Description | Hook cable clamp, for 12x5-7mm OD cable and 6x10-22mm, hooking on round ø8-25mm and flat 3-25mm |

General Specifications

| | |
|-------------------|---------------------|
| Metal Material | Stainless Steel 304 |
| Block Material | PA6 |
| Block Color | Black |
| Cables Per Hanger | 18 |

Dimensions

| | |
|--------------------------------|-------------------|
| Height | 285 mm 11.22 in |
| Width | 45.0 mm 1.77 in |
| Length | 56.7 mm 2.23 in |
| Compatible Cable 1 OD, maximum | 7.0 mm 0.275 in |
| Compatible Cable 1 OD, minimum | 5.0 mm 0.625 in |
| Compatible Cable 2 OD, maximum | 22.0 mm 0.87 in |
| Compatible Cable 2 OD, minimum | 10.0 mm 0.39 in |

Environmental Specifications

| | |
|-----------------------------------|-------------------------------------|
| Operating Temperature | -40°C to +85°C(-40°F to+185°F) |
| Environmental Strength Capability | Double Cable Weight |
| UV Resistance | ≥720 Hours, base on ISO4892.3-1994 |
| Vibration Test | ≥6 Hours,base on IEC 60068-2-6-2007 |

Packaging and Weights

| | |
|----------------|-------------------|
| Height, Packed | 320 mm 12.60 in |
|----------------|-------------------|

| | |
|--------------------------------------|--|
| Width, Packed | 220 mm 8.66 in |
| UOM | 1 Pcs |
| Packaging | Bag |
| Weight, Gross | 0.302 kg 0.666 lbs |
| Certifications and Compliance | |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |

