

Hook Cable Clamp, M Type, 4 holes, 1x10-11mm+3x12-22mm

- Easy and quick installation
- Robust design & material for outdoor use
- Operation Temperature -40~85 °C
- Hooking on round ø8-25mm and flat 3-25mm



Product Classification

| | |
|--------------------|---|
| Item Number | 6007322 |
| Part Number | - |
| Detail Description | Hook cable clamp, for 1x10-11mm OD cable and 3x12-22mm OD cable, hooking on round ø8-25mm and flat 3-25mm |

General Specifications

| | |
|-------------------|---------------------|
| Metal Material | Stainless Steel 304 |
| Block Material | PA6 |
| Block Color | Black |
| Cables Per Hanger | 4 |

Dimensions

| | |
|--------------------------------|---------------------|
| Height | 255.0 mm 10.04 in |
| Width | 41.5 mm 1.63 in |
| Length | 33.0 mm 1.30 in |
| Compatible Cable 1 OD, maximum | 11.0 mm 0.43 in |
| Compatible Cable 1 OD, minimum | 10.0 mm 0.39 in |
| Compatible Cable 2 OD, maximum | 22.0 mm 0.86 in |
| Compatible Cable 2 OD, minimum | 12.0 mm 0.47 in |

Environmental Specifications

| | |
|-----------------------------------|-------------------------------------|
| Operating Temperature | -40°C to +85°C(-40°F to+185°F) |
| Environmental Strength Capability | Double Cable Weight |
| UV Resistance | ≥720 Hours, base on ISO4892.3-1994 |
| Vibration Test | ≥6 Hours,base on IEC 60068-2-6-2007 |

Packaging and Weights

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.
The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.
Revised: Sep 19, 2024
Public

| | |
|--------------------------------------|--|
| Height, Packed | 320 mm 12.60 in |
| Width, Packed | 220 mm 8.66 in |
| UOM | 1 Pcs |
| Packaging | Bag |
| Weight, Gross | 0.203 kg 0.448 lbs |
| Certifications and Compliance | |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |

