

Termination Microwave, 10W, N Male

- Wide Frequency Range from DC to 3GHz
- With N male connector



Product Classification

| | |
|--------------------|------------------------------------|
| Item Number | 6009644 |
| Part Number | - |
| Detail Description | Termination microwave, 10W, N Male |

General Specifications

| | |
|--------------------|----------------------------|
| Connector Material | Brass Ternary Alloy Plated |
| Pin Material | Brass Silver Plated |
| Housing Material | Aluminium Black Anodised |
| Connector Type | N Male |

Dimensions

| | |
|----------------|-------------------|
| Length | 48.5 mm 1.91 in |
| Outer Diameter | 30.0 mm 1.18 in |

Electrical Specifications

| | |
|-------------------|--|
| Nominal Impedance | 50 Ω |
| Power | 10 Watts |
| Peak Power | ≥5kW (1μs pulse width 0.2% duty cycle) |
| Frequency Range | DC-3GHz |
| Max VSWR | ≤1.15:1 |

Environmental Specifications

| | |
|-----------------------|--------------------------------------|
| Operating Temperature | -55°C to +125 °C (-67 °F to +257 °F) |
|-----------------------|--------------------------------------|

Packaging and Weights

| | |
|----------------|----------------------|
| Height, Packed | 60 mm 2.36 in |
| Width, Packed | 50 mm 2.36 in |
| UOM | Pcs |
| Packaging | Carton |
| Weight, Gross | 0.072 kg 0.159 lbs |

Certifications and Compliance

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.
The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.
Revised: Apr 10, 2025
Public

| | |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |

