

90° Copper Lug, AWG 2/0#, one hole 3/8", standard barrel, with inspection window, black

- Copper cable lugs are designed for connecting copper cables, coils and Bus-bars
- Copper Tube Terminals between 6mm² & 800mm² have bell entry to ensure easy entry even for flexible conductors.
- Incorporates inspection window to check the correct cable positioning.
- The barrel length has been designed to allow easy and accurate positioning of the dies during the crimping operation.
- "colour code" help choose the right connector, the colour name is also printed in order to avoid problems for those who are colour-blind.




Product Classification

Item Number	6009726
Part Number	-
Detail Description	90°Copper Lug, AWG 2/0#, one hole 3/8", standard barrel, with inspection window,black

General Specifications

Colour Code	Black
Material	Copper
Tongue Type	Standard
Tongue Angle	90 degree
Surface	Tin-plated
Inspection Window	With inspection window

Dimensions



Bolt Size	3/8 in 10.2 mm
Tang Width (C)	0.83 in 21.0 mm
Barrel length (B)	0.94 in 23.9 mm
Overall length (L)	1.64 in 41.7mm
Inner diameter (ID)	0.45 in 11.4 mm

Outer diameter(OD) 0.56 in | 14.2 mm

Electrical Specifications

Rating - Maximum Voltage 35KV

Environmental Specifications

Operating Temperature -40 °C to +90°C (-40 °F to +212 °F)

Storage Temperature -40 °C to +80 °C (-40 °F to +176 °F)

Packaging and Weights

Included Lug

Packaging Quantity and UOM 1 pcs

Piece Weight 0.13 lb | 0.06 kg

Certifications and Compliance

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

RoHS Compliant

UL Compliant