Grounding Kit, Universal Type, 1/4"-1-5/8", 0.5 Meter

- **Easy and quick installation**
- **Low contact transition resistance of maximum 10mΩ**
- **Operation Temperature -40~70 ℃**
- **Waterproof IP68**

Product Classification	
Item Number	6003350
Part Number	-
Detail Description	Grounding Kit, universal type, for 1/4"-1-5/8" cable, 0.5 meter, installation accessories including
General Specifications	
Bonding Conductor Material	Copper
Bonding Conductor Wire Size	AWG 6
Grounding Strap Material	Copper, Tin Plated
Lug Type	One-hole lug
Screw Material	Stainless Steel
Flat washer Material	Stainless Steel
Spring washer Material	Stainless Steel
Nut Material	Stainless Steel
PVC tape Material	PVC
Butyl Rubber Tape Material	Butyl
Dimensions	
Bonding Conductor Length	0.5 m | 19.7 in
Lug Hole Size	M8
Screw Size	M8 x 25 mm
Suitable Cable	1/4” - 1-5/8”
Environmental Specifications	
Operating Temperature	-40°C to +70 °C (-40 °F to +158 °F)
Weatherproofing Method	Butyl and electric tape
Electrical Specifications	

TEMPLATE# ITM0401 VERSION A/8 DATE 08/20/2024

©Maxdao Inc. All rights reserved.
The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.
Revised: Nov 19, 2024
Public

Contact Transition Resistance	Maximum 10mΩ
Packaging and Weights	
Height, Packed	320 mm | 12.60 in
Width, Packed	220 mm | 8.66 in
Included	Grounding kit | Hardware | Lug | One roll of PVC tape | One roll of butyl rubber tape
UOM	Kit
Packaging	Bag
Weight, Gross	0.23 kg | 0.507 lbs
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

TEMPLATE# ITM0401 VERSION A/8 DATE 08/20/2024

©Maxdao Inc. All rights reserved.
The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.
Revised: Nov 19, 2024
Public