

Grounding Kit, Standard Type, 1/4"-5/8", 0.6 Meter

- Easy and quick installation
- Low contact transition resistance of maximum 10mΩ
- Operation temperature -40~70 °C
- Waterproof IP68



Product Classification

Item Number	6009768
Part Number	-
Detail Description	Grounding kit, standard type, for 1/4"-5/8" cable, 0.6 meter, installation accessories included

General Specifications

Bonding Conductor Material	Copper
Bonding Conductor Wire Size	AWG 6
Braided Ground Strap Material	Copper, Tin-plated
Lug Type	One-hole lug
Screw Material	Stainless Steel
Flat washer Material	Stainless Steel
Spring washer Material	Stainless Steel
Nut Material	Stainless Steel

Dimensions

Bonding Conductor Length	0.6 m 23.62 in
Lug Hole Size	M8
Screw Size	M8x25 mm
Suitable Cable	1/4"-5/8"

Environmental Specifications

Operating Temperature	-40°C to +70 °C (-40 °F to +158 °F)
Weatherproofing Method	Butyl and electric tape

Electrical Specifications

Contact Transition Resistance	Maximum 10mΩ
-------------------------------	--------------

Packaging and Weights

Height, Packed	320 mm 12.60 in
Width, Packed	220 mm 8.66 in

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Mar 6, 2026
 Public

Included	Grounding kit Hardware Lug One roll of PVC tape One roll of butyl rubber tape Silicone grease
UOM	Kit
Packaging	Bag
Weight, Gross	0.487 kg 1.073 lbs

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

