

Cold Shrink Tube, $\phi 40 \times 280 \text{ mm}$, Black

- Easy and quick installation
- Manufactured from silicone rubber
- Suitable for a wide range of cable sizes
- No special tools or training required for installation
- Offering good mechanical, insulation and sealing protection



Product Classification

Item Number	6009277
Part Number	-
Detail Description	Cold shrink tube, $\phi 40 \times 280 \text{ mm}$, black

General Specifications

Material	Silicone
Cable type	Corrugated Elliptical Waveguide Smoothwall
Cable Range	$\phi 10.5\text{-}32 \text{ mm}$ 0.413-1.26 in
Color	Black
Mastic(Y/N)	N
Shrink Ratio	4:1

Dimensions

Length Before Shrink	280 mm 11.02 in
Length After Shrink	320 mm 12.60 in
Inner Diameter Before Shrink(ID)	40 mm 1.57 in
Inner Diameter After Shrink(ID)	8 mm 0.315 in
Thickness After Shrink	3.1 mm 0.12 in

Environmental Specifications

Operating Temperature	-60 °C to +90 °C (-76 °F to +194 °F)
Weatherproof Resistance	IP68, based on ISO20653:2013
UV Resistance	≥ 1000 hours, base on ASTM G154-16

Packaging and Weights

Height, Packed	300 mm 11.81 in
Width, Packed	70 mm 2.75 in
UOM	1 Pcs
Packaging	Bag



Weight, Gross	0.122 kg 0.269 lbs
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

