

## Grounding Kit, Tinned Clip-on Type, 1/2", 1.22 Meter, With Two 3/8" Hole Lug, With Conductive Silicone Grease

- Easy and quick installation
- Low contact transition resistance of maximum 10mΩ
- Operation temperature -40~70 °C
- Waterproof IP68



### Product Classification

Item Number	6009810
Part Number	-
Detail Description	Grounding kit, tinned clip-on type, for 1/2" cable, cable length 1.22m, installation accessories included and conductive silicone grease

### General Specifications

Bonding Conductor Material	Copper
Bonding Conductor Wire Size	6 AWG
Grounding Strap Material	Copper, Tin plated
Lug Type	Two-hole lug
Screw Material	Stainless Steel
Flat Washer Material	Stainless Steel
Spring Washer Material	Stainless Steel
Nut Material	Stainless Steel
Tape Material	PVC & Butyl

### Dimensions

Bonding Conductor Length	1.22 m   4 feet
Lug Hole Size	10.2 mm   0.40 in
Screw Size	3/8"x1"
Suitable Cable	1/2"

### Environmental Specifications

Operating Temperature	-40°C to +70 °C (-40 °F to +158 °F)
Weatherproofing Method	Butyl and electric tape

### Electrical Specifications

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Sep 26, 2024  
 Public

---

Contact Transition Resistance	Maximum 10mΩ
-------------------------------	--------------

---

**Packaging and Weights**

---

Height, Packed	320 mm   12.60 in
----------------	-------------------

---

Width, Packed	220 mm   8.66 in
---------------	------------------

---

Included	Grounding kit   Hardware   One roll of PVC tape   One roll of butyl rubber tape   One conductive silicone grease
----------	--

---

UOM	Kit
-----	-----

---

Packaging	Bag
-----------	-----

---

Weight, Gross	0.756 kg   1.666 lbs
---------------	----------------------

---

**Certifications and Compliance**

---

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
---------------	--

---

RoHS	Compliant
------	-----------

---

