

Whipcheck Safety Cable, Hose To Hose, Galvanized Steel, 1/2" To 2" Hose Size

- Whipchecks are commonly used on hose for air, water blast, drilling, steam, concrete, sandblast or other high pressure applications
- Whipchecks should be installed in the fully extended position (no slack) for proper safety assurance
- Hose to hose restraints is slipped over the hose on each side of the fitting and prevent hose whip in the event of fitting separation or failure
- CE certified



Classification

| | |
|--------------------|--|
| Material Number | 6005870 |
| Part Number | HHB3 |
| Status | Active |
| Detail Description | Whipcheck safety cable, hose to hose, galvanized steel ,1/2" to 2" hose size |

Details

| | |
|------------------------|-------------------------------------|
| Cable Range | 1/2-2 in 12.70-50.80 mm |
| Length | 28.0 in 711.2 mm |
| Max. Working Pressure | 200 psi |
| Approx. Break Strength | 2800 lbs 1270 kg |
| Working Load | 560 lbs 254 kg (Safety Factor 5*) |
| Material Type | Galvanized Steel |

Package

| | |
|---------------|---------------------|
| UOM | 1 pcs |
| Packaging | Bag |
| Weight, gross | 0.448 lb 0.203 kg |

Certifications

| | |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |
| CE | Compliant |